1. (Currently Amended) A fan housing mounted on a frame of a system, comprising:

a main body having:

a first section of the main body having a through hole;

a second section disposed on the main body, wherein and having a recess having a

specified size is located between the first and second sections aligned with the through hole:

a fixing portion formed in the recess a gap formed between the first and second sections;

and

a fastening structure passing through the first section via the through hole, partially

disposed in and having one end accommodated by the recess and having a part with disposed in

the gap and having a profile corresponding to that of the recess and having a size substantially

identical to the specified size of the recess for precisely positioning the part in the recess so that

the part substantially fills the entire recess gap;

wherein the recess of the second section prevents the one end of the fastening structure

from being exposed.

2. (Previously Presented) The fan housing as claimed in claim 1, wherein the fixing

portion prevents the fastening structure from rotating and limits the position of the fastening

structure

3. (Previously Presented) The fan housing as claimed in claim 2, wherein the fastening

structure includes a screw and the part is a nut disposed in the gap and having the profile 2

Application No. 10/779,674

Amendment dated July 16, 2008

Reply to Office Action of April 16, 2008

substantially identical to that of the gap, the nut is in aligned with the through hole by the fixing

portion, the screw passes through the through hole and engages with the nut, and the first and

second sections prevent the nut from moving along an axial direction of the screw.

4-5. (Canceled).

6. (Previously Presented) The fan housing as claimed in claim 1, wherein the main body

is rectangular, and the first and second sections, the fixing portion and the fastening structure are

disposed at corners of the main body.

7. (Currently Amended) The fan housing as claimed in claim [[24]] 1, wherein the part is

a hook passing through the through hole and connected to the gap for mounting the fan housing

on the frame in the system.

8. (Canceled)

9. (Previously Presented) The fan housing as claimed in claim 1, wherein the main body,

the first and second sections and the fixing portion are a monolithic piece formed by injection

molding.

3

PCL/RJW/jmc

Docket No.: 0941-0918P

Reply to Office Action of April 16, 2008

10. (Original) The fan housing as claimed in claim 1, further comprising a base at a

bottom of the main body, wherein a plurality of ribs or stator blades are disposed between the

base and the main body for guiding an air flow.

11. (Previously Presented) The fan housing as claimed in claim 10, wherein the ribs or

stator blades have the same inclined angle.

12. (Currently Amended) A fan assembly, comprising:

a rotor; and

a fan housing having a base to receive the rotor, the fan housing comprising:

a main body;

a first section disposed on the main body and having a through hole;

a second section disposed on the main body, wherein a gap is formed between the first

and second sections; and

a fixing portion formed in the gap; and

a non-threaded-fastening structure passing through the first section via the through hole

and having a part with a profile substantially equal to that of the gap for positioning the part

preventing the part from sliding in the gap;

wherein the second section prevents one end of the fastening structure from being

exposed.

4

PCL/RJW/jmc

Application No. 10/779,674

Amendment dated July 16, 2008

Reply to Office Action of April 16, 2008

13. (Previously Presented) The fan assembly as claimed in claim 12, wherein the fixing

portion prevents the fastening structure from rotating and limits the position of the fastening

structure.

14-16. (Canceled)

17. (Previously Presented) The fan assembly as claimed in claim 12, wherein the main

body is rectangular, and the first and second sections, the fixing portion and the fastening

structure are disposed at corners of the main body.

18. (Previously Presented) The fan assembly as claimed in claim 12, wherein the part is a

hook passing through the through hole and connected to the gap for mounting the fan housing on

the frame in the system.

19. (Canceled)

20. (Original) The fan assembly as claimed in claim 12, wherein the main body, the first

and second sections and the fixing portion are an integral structure formed by injection molding.

21. (Original) The fan assembly as claimed in claim 12, wherein the base at a bottom of

the main body supports the rotor, a plurality of ribs or stator blades are disposed between the

base and the main body for guiding an air flow.

5

PCL/RJW/imc

Docket No.: 0941-0918P

22. (Previously Presented) The fan assembly as claimed in claim 21, wherein the ribs and stator blades have the same inclined angle and shape similar to those of rotor blades of the rotor.

23. (Currently Amended) A fan assembly comprising:

a rotor:

a fan housing receiving the rotor therein and having a main body with a first section, having a hole, and a second section, wherein a gap is formed between the first and second

sections; and

a non-threaded-fastening structure having a hook passing through the hole to connect the gap or joining the gap from outside of the fan housing so as to fix the fan assembly to an external system frame.

24. (Currently Amended) A fan housing mounted on a frame of a system, comprising:

a main body;

a first section of the main body having a through hole;

a second section disposed on the main body, wherein and having a recess is located

between the first and second sections through hole; and

a fixing portion formed in the recess; and

a non-threaded fastening structure passing through the first section via the through hole,

partially disposed in the gap and having a part with a profile corresponding to that of the recess

for precisely positioning the part in one end accommodated by the recess,

Application No. 10/779,674 Amendment dated July 16, 2008 Reply to Office Action of April 16, 2008

wherein the second section prevents the one end of the fastening structure from being exposed.

Docket No.: 0941-0918P